

# AGROFARM G



85-100-115




Agrofarm G		85	100	115
<b>ENGINE</b>				
Emissions		Stage I	Stage I	Stage II
Manufacturer		SDF 1000.4 W	SDF 1000.4 WT	SDF 1000.4 WT1
Cylinders/Capacity	No./cc	4/4000	4/4000	4/4000
Naturally aspirated		●	-	-
Turbocharged intake		-	●	●
Turbo Intercooler intake		-	-	●
Max. homologated power (ECE R120)	kW/hp	61/83	70,6/96	81/110
Max. engine speed (rated)	rpm	2350	2300	2350
Max. torque	Nm	257	342	396
Engine control mechanical		●	●	-
Engine control electronically		-	-	●
Cyclone prefilter		○	○	○
Cooling liquid		●	●	●
Fuel tank capacity	litres	150	150	150
<b>MECHANICAL GEARBOX</b>				
Synchromesh		●	●	●
Number of speeds with supercreeper gear	n°	20+20	20+20	20+20
Minimum/maximum speed with supercreeper gear	km/h	1,85/0,20	2,01/0,22	2,01/0,22
Number of speeds with Hi-Lo and creeper Max. speed	n°	40+40	40+40	40+40
Max. speed	km/h	40	40	40
Mechanical dry clutch, single		●	●	●
<b>REAR PTO</b>				
Multiplate wet clutch / Electrohydraulic control		●/●	●/●	●/●
PTO 540/1000		●	●	●
PTO 540/540ECO/1000/1000ECO		○	○	○
Ground speed PTO		○	○	○
<b>FRONT AND REAR AXLE</b>				
4WD and differential lock electrohydraulically operated		●	●	●
Steering angle 2WD / 4WD	degrees	65°/50°	65°/55°	65°/55°
<b>BRAKES</b>				
Braking system with wet brake discs		●	●	●
Mechanical parking brake		●	●	●
<b>STEERING</b>				
Hydrostatic steering with independent pump		●	●	●
<b>HITCH</b>				
Category		II	II	II
Rear hitch mechanical		●	●	●
Rear hitch lift capacity	kg	2150	4200	4200
<b>HYDRAULIC SYSTEM</b>				
Open-centre hydraulic system	l/min	56	56	56
Mechanical rear auxiliary distributors	No. of ways	2/4/6/8	2/4/6/8	2/4/6/8
<b>DRIVING POSITION</b>				
Side control levers		●	●	●
Cab and/or ROPS		●	●	●
ROPS with sun shade		○	○	○
Driver seat with mechanical suspension		●	●	●
Instrumentation analogue		●	●	●
<b>DIMENSIONS AND WEIGHTS</b>				
Standard rear tyres		420/85R30"	420/85R30"	420/85R30"
Max. length	mm	3850	3850	3990
Width (min.-max.)	mm	2050-2458	2050-2458	2050-2458
Wheelbase (4WD/2WD)	mm	2310/2290	2310/2290	2340/2320
Front track (min.-max.) 2WD	mm	1600-2100	1600-2100	1600-2100
Front track (min.-max.) 4WD	mm	1630-2030	1630-2030	1630-2030
Rear track (min.-max.)	mm	1602-2002	1602-2002	1602-2002
Max height at ROPS / with cab	mm	2710/2740	2790/2790	2790/2790
Weight with ROPS (4WD/2WD)	kg	3760/3120	4120/3540	4120/3540
Weight with cab (4WD/2WD)	kg	4100/3260	4460/3680	4660/3680
Maximum load capacity (4WD/2WD)	kg	6100/4800	6100/4800	7200/5300

● = standard ○ = optional - = Not available

The technical data and pictures are guideline only. Committed to delivering a product more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time without notice.

To discover more please contact your dealer or visit [deutz-fahr.com](http://deutz-fahr.com).

DEUTZ-FAHR is a brand of  SDF

