



TECHNICAL DATA		6145W HD
ENGINE		
Manufacturer		Yuchai
Model		YC6 140-S300
Emissions		Stage IIIA
Cylinders/Displacement	nº/cc	6/6494
Intake		Turbo Intercooler
Injection		Common Rail
Max. power	kW/HP	103/140
Maximum torque	Nm	560
Electronic engine governor		•
Cyclone pre-filter		•
Fuel tank capacity	litres	270
TRANSMISSION		
Number of speeds		24+12
Number of speeds with supercreeper gear		16+12
Minimum speed with supercreeper gear	km/h	0,43
Maximum speed	km/h	40
PTO	KIII/II	40
Independent PTO		•
Mechanically actuated PTO		•
Rear 540/1000 PTO		•
FRONT AND REAR AXLE		·
Carraro front axle		•
Mechanically operated 4WD		Š
Self-locking front differential		
Mechanically operated diff. Lock		•
BRAKES AND STEERING		
Oil-immersed disc brakes		•
Hydrostatic steering		•
REAR LIFT		•
Mechanical rear lift control		•
	le er	5000
Maximum rear lift capacity	kg	5000
3-point hitch with automatic upper and lower links		•
HYDRAULIC SYSTEM		•
Open centre hydraulic system	l/min	80
Hydraulic pump flow	ı/min n°	3
Auxiliary rear mechanical distributors	n°	3
DRIVING POSITION		•
Side mounted control levers		
Silent-Block mounted cab		•
Air conditioning		•
Driver seat with mechanical suspension		•
Analogue dashboard		•
DIMENSIONS AND WEIGHTS		
Width (minmax.)	mm	2380-2466
Wheelbase	mm	2805
Total unladen weight	kg	5500

 $\bigcirc =$ standard $\bigcirc =$ optional - = Not available

The technical data and pictures are guideline only. Committed to delivering a product more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time without notice.

