

AGGROFARM 5 SERIES



5095 // 5105 // 5105 HD
5115 // 5125

LRC



**DEUTZ
FAHR**

TECHNICAL DATA		AGROFARM				
		5095	5105	5105 HD	5115	5125
ENGINE						
Type				FARMotion		
Emission level				LRC		
Cylinders/Displacement	n°/cc			4/3849		
Bore/Stroke	mm			103/115.5		
Aspiration				Turbo Intercooler		
Injection @ pressure	Type			Common Rail @ 2000 bar		
Max. power @ 2000 rpm	kW/HP	71/97		78/106	85/116 93/126	
Rated power @ 2200 rpm	kW/HP	57.3/92		74/101	80.6/110 88/120	
Max torque @ 1600 rpm	Nm	386		425	462 508	
Torque rise	%			32	31	
Visco cooling fan				●		
Standard cooling fan				○	-	
Fuel tank	l			145		
TRANSMISSION						
SDF transmission	Type	T4330		T4350	T5350	
Gearbox	n°	5 gears x 2 or 4 ranges				
MECHANICAL SHUTTLE						
Shuttle	Type	Mechanical with lever under steering wheel				
N° of speed (4 ranges)	n°	20+20				
N° of speed with Hi-Lo (2 ranges)	n°	20+20 Hi-Lo				
N° of speed with Hi-Lo (4 ranges)	n°	40+40 Hi-Lo				
HYDRAULIC SHUTTLE						
PowerShuttle	Type	Hydraulic with lever under steering wheel				
Adjust. response of PowerShuttle		5 different setting				
N° of speed (4 ranges)	n°	20+20				
N° of speed with Hi-Lo (2 ranges)	n°	20+20 Hi-Lo				
N° of speed with Hi-Lo (4 ranges)	n°	40+40 Hi-Lo				
Stop&Go				●		
ComfortClutch				●		
PTO						
Electrohydraulic engagement				●		
540/540ECO			●		-	
540/540ECO/1000/1000ECO			-		●	
LIFT						
Mechanical rear lift			●		-	
Mechanical rear lift with EasyLift			○		-	
Electronic rear lift			-		●	
Rear lifting capacity (STD)	kg			3600		
Rear lifting capacity (OPT)	kg		4525		5410	
HYDRAULICS						
Pump flow	l/min			55		
Rear spool valves	n°		2/3		3	
BRAKES						
4 wheel braking				●		
Mechanical parking brake				●		
Hydraulic trailer brake				○		
FRONT AXLE						
Front axle	Size	1.5			2	
Steering angle	degrees	50			55	
Electrohydraulic 4WD engagement				●		
Electrohydraulic Diff. Lock engagement				●		
CAB						
4 pillar cab				●		
Standard roof				●		
High visibility roof				○		
High visibility roof - FOPS				○		
Hydro Silent-Block suspension				●		
Manual A/C				●		
Mechanical suspended seat		●			-	
Pneumatic suspended seat		○			●	
DELUXE pneum. suspended seat				○		
Passenger seat		○			●	
External controls for PTO and lift		○			●	
Radio				●		
DIMENSIONS AND WEIGHTS						
Wheelbase	mm			2400		
Max. length	mm			4268		
Centre rear axle - cab	mm			1968		
Weight	kg	4000		4250	4350	
Front admissible load	kg	2900			3000	
Rear admissible load	kg	3700		4000	5000	
Total admissible load	kg	6500		7000	7500	

● = standard ○ = optional - = not available

The technical data and pictures are guideline only. Committed to delivering a product more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time without notice.