

DEUTZ-FAHR 3035 E - 3040 E - 3042 E




Technical data	3E Series		
	3035 E	3040 E	3042 E
ENGINE			
Emissions		Bharat Trem 3A	Bharat Trem 3A
Manufacturer		S324	S325.1
Cylinders/Displacement	n°/cm³	3/2400	3/2500
Naturally aspirated		●	●
Max power	kW/HP	26.8/36	31.3/42
Rated power	rpm	2000	2000
Max torque	Nm	137.4	165.8
Engine control mechanical		●	●
Cooling system		●	●
Silencer with vertical exhaust		●	●
Fuel tank capacity	liters	55	55
MECHANICAL GEARBOX			
Synchronised		●	●
Differential lock		-	Mechanically operated
Number of speeds	n°	8+2	8+2
Min speed	Km/h	2,61	2,61
Max speed	Km/h	31,96	31,96
Mechanical clutch dry, single		●	●
REAR PTO			
Mechanical clutch dry, single		●	●
PTO 540		●	●
FRONT AND REAR AXLE			
Fixed front axle		●	●
Steering angle	degrees	50°	50°
BRAKES			
Mechanically operated		●	●
Oli immersed disc brake		●	●
Mechanical parking brake		●	●
STEERING			
Mechanical steering		●	●
HITCH			
Category		II	II
Rear hitch mechanical		●	●
Rear hitch lift capacity	kg	1250	1250
Easy lift		●	●
HYDRAULIC SYSTEM			
Pump output (std)	L/min	24	24
Open centre hydraulic system		●	●
Tipping system		●	●
DRIVING POSITION			
Side control levers		●	●
Fixed operator seat		●	●
DIMENSIONS AND WEIGHTS			
Standard rear tyres		12.4-28"	12.4-28"
Length	mm	3220	3220
Width	mm	1600	1600
Height	mm	2185	2195
Wheelbase	mm	1800	1800
Front track	mm	1260	1260
Rear track	mm	1300	1330
Ground clearance	mm	400	410
Weight	kg	1620	1660

● STD

The technical data and pictures are guideline only. Committed to delivering a product more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time without notice.

DEALER

To discover more please contact your dealer
or visit deutz-fahr.com.

DEUTZ-FAHR is a brand of  SDF

